

Very high temperature self-regulating heating cable.

FailSafe Super Inherently Temperature-Safe Heating Cable

- Automatically adjusts heat output in response to increasing or decreasing pipe temperature.
- Can be cut-to-length.
- Inherently temperature safe.
- Suitable for use in safe, hazardous and corrosive areas.
- High power outputs to 75W/m at 10°C.
- Full range of controls and accessories available.

DESCRIPTION

FAILSAFE SUPER is a very high temperature self-regulating heating cable, having an exposure limit of 225°C, energised or not.


FAILSAFE SUPER is provided with a metal braid for flexibility and a thermoplastic or fluoropolymer outer jacket.

Easy terminations, cut-to-length.

Safest ever self-regulating product range for very high temperature exposure; will not overheat even when exposed to 225°C when energised or switched off as it is *inherently temperature-safe*.

FAILSAFE SUPER is approved for use in non-hazardous, hazardous and corrosive environments to worldwide standards.

ATEX/ IECEx Approved.



INHERENTLY TEMPERATURE-SAFE

“ The inherent ability to self-regulate at a temperature level below the maximum product rating and withstand temperature of the insulating materials, without the need for temperature control.”

Similar competitor self-regulating products are typically limited to a maximum energised temperature, typically 120°C at which point, their retained power output prevent the cable from self-regulating at its own limiting temperatures. All such products require temperature control to ensure their own temperature safety.



SPECIFICATION

MAXIMUM CONTINUOUS EXPOSURE

TEMPERATURE: 225°C† (437°F)
(ENERGISED OR SWITCHED OFF)

MINIMUM OPERATING

TEMPERATURE: -65°C* (-85°F)

MINIMUM INSTALLATION

TEMPERATURE: -40°C (-40°F)

POWER SUPPLY: 12 - 277V AC

TEMPERATURE CLASSIFICATION:

15FSS, 30FSS, 45FSS & 60FSS @ nom 230V - T3 (200°C)
75FSS @ nom 230V - T2 (300°C)

INGRESS PROTECTION IP67

WEIGHTS & DIMENSIONS:

Type Ref	Dimensions (mm) +/-0.5	Weight kg/100m	Min Bending radius	Gland size
FSS-C	10.55 x 4.35	10.4	30mm	M20
FSS-CF	11.45 x 5.25	13.4	35mm	M20

APPROVAL DETAILS:

ATEX† - CML 19ATEX3377
IECEX† - CML 19.0120
EAC*† - TC RU C-GB.MHO62.B.06041
FM - 3009080
CSA - 1295278, 1547590

ORDERING INFORMATION:

Example; 30 FSS 2 - C option F

Output 30w/m at 10°C
FSS Heating Cable
Supply Voltage 220 - 240V AC
Metal Braid
Outer Sheath, Fluoropolymer

ACCESSORIES:

Heat Trace supply a complete range of accessories including termination/splice kits, end seals, junction boxes and controls. Such items carry separate approvals from the heating cables. Use only approved components, as per system certification.

FURTHER INFORMATION:

Please consult the appropriate termination instructions and the Heat Trace Installation, Maintenance and Testing Manual (HTDIMM 010) for further details.

MAXIMUM LENGTH (m) vs. CIRCUIT BREAKER SIZE:

The following circuit details relate specifically for the trace heating of pipework and equipment. For any other application consult Heat Trace.

Cat Reference	Environmental Start-up Temp.	230V				
		10A	16A	20A	32A	50A
15FSS	10°C	76	122	154	172	172
	0°C	70	112	140	172	172
	-20°C	62	98	122	172	172
	-40°C	52	82	102	164	172
30FSS	10°C	52	82	102	122	122
	0°C	46	74	92	122	122
	-20°C	40	66	82	122	122
	-40°C	34	54	68	110	122
45FSS	10°C	38	62	76	100	100
	0°C	34	56	70	100	100
	-20°C	30	50	62	98	100
	-40°C	22	34	44	70	100
60FSS	10°C	30	50	62	86	86
	0°C	28	44	56	86	86
	-20°C	20	32	40	62	86
	-40°C	12	18	24	38	60
75FSS	10°C	24	40	50	76	76
	0°C	18	30	38	60	76
	-20°C	14	22	26	42	66
	-40°C	8	12	16	26	40

For use with Type C circuit breakers to IEC 60898.

These circuit lengths may be exceeded dependant on specific design parameters.

THERMAL RATINGS:

Nominal output at 230V when FSS is installed on thermally insulated carbon steel pipes. For 75W/m and above, the use of aluminium overfoiling is strongly recommended to optimise the thermal transmission to the pipe and achieve the stated thermal ratings.

