



FLUXO /BSR-TSE

Termination set in screwing technology for use in non-hazardous area.

Termination Set Non Ex

- Compact design
- Temperature resistant up to 130°C
- Quick and easy to assemble
- Suitable for different types of heating tapes FSLe;FSR;FSWE;FSS;FSU (up to 130°C)
- Power supply and end termination separately available

Description

The Fluxo system contains a termination set which is easy and fast to assemble, based on approved screw technology. The compact dimensions make it possible, that this system can be installed even underneath the thermal insulation of the pipe.

The BSR-TSE product range contains several components such as power supply, end termination, branches and connections.

The installation is very easy to handle and requires no special tools.



Technical Data

Temperature Resistant:	-40°C... 130°C
For Heating Tapes:	FSLe;FSR;FSWE, FSS;FSU; EMTS
Cross Section:	up to 2.5mm ²
Length Power Connection:	125mm
Length End Termination:	58mm

Further Information

Please consult the installation instructions!

Ordering Information

Part number:	
CON5SS:	Power connection and end termination set
CON5SA:	Power connection (single)
CON5SE:	End termination (single)
CON5ST:	T-Branch (supply cable + 2 heating cables or 3 heating cables)
CON5SV:	Connection heating cable – heating cable,

Alternative Products

Part number:	
BSR T S E:	Non-Ex termination set in shrinking technology